

Smart Film™

Lámina inteligente PDLC



info@laminaprotect.com
www.laminaprotect.com

Smart Film™



Datos técnicos

VLT (Transmitancia de luz paralela)	OFF	3%±1%	
	ON	85%±1%	
Transmitancia total	ON	82%/88%	
	OFF	65%±1%	
Transparencia	ON	<3%±1%	
	OFF	>95%±1%	
Transparencia 45°	ON	8-11%	
Ancho Máximo		≤1840mm	
Grosor		0.35-0.55mm	
Tiempo encendido y apagado	ON	200ms	
	OFF	220ms	
Modos		ON/OFF/DIM	
Voltage		AC60V	
Alimentación		AC100-120V60Hz / 220-240V50Hz	
Consumo	ON	avg. 4-6W/m2	
Temperatura recomendada		-20°C to +110°C	
Bloqueo de IR		85%	
Bloqueo de UV		99%	
Angulo de visión	ON	160°+1%	
Tolerancia Largo		+0.5/-0 meter	+0/-2mm
Tolerancia Ancho		+5/-0mm	+0/-2mm

Aplicaciones



► Oficina





 **Hotel**



▶ Centros de atención



► Hospital



Smart Film™

Lámina inteligente PDLC



info@laminaprotect.com
www.laminaprotect.com